

Warning Blinkers

Salient Features

- Portable radiation alert Unit
- Dual operation – Mains with adapter and Battery operated
- Rigid battery life for audio and visual alarms
- Works for the X-ray & Gamma ray detection
- Green flash when radiation detected
- Red flash when no radiation
- In-built Rechargeable battery
- Low battery indication



Technical Specifications:

	DBS I	DBS II
Operation voltage	: DC 6V.	DC 6V.
Inbuilt battery	: 6V 4.5AH.	6V 4.5AH.
Mains power source	: 110/240V (50 Hz/60 Hz).	110/240V (50 Hz/60 Hz).
Charging duration	: 3-4 hours.	3-4 hours.
Effective visual range	: 200 - 300 meters.	100 - 200 meters.
Light type	: Flash 60 time per minute.	Flash 60 time per minute.
Sound power level	: ≥ 90dB.	≥ 90dB.
Working time	: 6 - 8 hours.	4 - 6 hours.
Light Beacon color	: Red Beacon(only warning)	Green (No Detection), Red (Radiation detection).
Measurement (LxWxH)	: 175x 175 x 320mm.	250x 110 x 280mm.
Battery indication	: Low battery indication.	Low battery indication.
Operating temperature	: -10 to 60°C (14 to 140°F).	-10 to 60°C (14 to 140°F).
Warranty	: 6 Months.	6 Months.
Geiger Muller detector	: N A	Gamma detector.
Threshold	: N A	Variable 3 mR (As per customer requirement).
Weight	: 3Kg	2.5Kg